

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	FERODO Brake Fluid
Registration number	-
Synonyms	Brake Fluid DOT 3 & DOT 4 (Boiling Points <260°C)
Product code	FBC050, FBC050A, FBC050B, FBC100, FBC100A, FBC100B, FBX025, FBX045EUR, FBX050, FBX050A, FBX050B, FBX100, FBX100A, FBX100B, FBX500, FBX500A, FBX500B, FBX2000
Issue date	22-May-2013
Version number	08
Revision date	17-June-2024
Supersedes date	-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Hydraulic fluid in automotive brake/clutch system.
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer/Supplier

Company name	Federal-Mogul Global Aftermarket EMEA bv
Address	Prins Boudewijnlaan 5 B-2550 Kontich Belgium
Telephone	+32 3 450 83 10
Contact person	Braking_EMEA@DRiV.com
1.4. Emergency telephone number	3E Global Incident Response Hotline  +44 20 35147487 Access code: 335908

**General emergency** 112 or 999 SDS/Product information may not be available for the Emergency Service.

**Non-emergency medical helpline** 111 SDS/Product information may not be available for the Emergency Service.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Health hazards

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Reproductive toxicity (fertility, the unborn child)	Category 2	H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate

#### Hazard pictograms



#### Signal word

Warning

## Hazard statements

H319 Causes serious eye irritation.  
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

## Precautionary statements

### Prevention

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P264 Wash thoroughly after handling.

### Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Storage

None.

### Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Supplemental information on the label

None.

## 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Triethylene glycol monobutyl ether	25 - 40	143-22-6 205-592-6	01-2119475107-38-XXXX	603-183-00-0	
<b>Classification:</b> Eye Dam. 1;H318 <b>Specific Concentration Limits:</b> Eye Dam. 1;H318: C ≥ 30 %, Eye Irrit. 2;H319: 20 % ≤ C < 30 %					
Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	15 - 25	30989-05-0 250-418-4	01-2119462824-33-XXXX	-	
<b>Classification:</b> Repr. 2;H361fd					
Diethylene glycol	10 - 15	111-46-6 203-872-2	01-2119457857-21-XXXX	603-140-00-6	#
<b>Classification:</b> Acute Tox. 4;H302					
3,6,9,12-Tetraoxahexadecan-1-ol	5 - 10	1559-34-8 216-322-1	01-2120768763-41-XXXX	-	
<b>Classification:</b> Eye Irrit. 2;H319					
2-(2-Butoxyethoxy)ethanol	1 - 3	112-34-5 203-961-6	01-2119475104-44-XXXX	603-096-00-8	#
<b>Classification:</b> Eye Irrit. 2;H319					
2-(2-Methoxyethoxy)ethanol	< 0.25	111-77-3 203-906-6	01-2119475100-52-XXXX	603-107-00-6	#
<b>Classification:</b> Repr. 1B;H360D <b>Specific Concentration Limits:</b> Repr. 1B;H360D: C ≥ 3 %					

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Community workplace exposure limit(s).

#### Composition comments

Classification of this product as Serious eye irritation Category 2 (H319) is based on tests conducted on the product as a whole, rather than calculations based on ingredients.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

#### 4.1. Description of first aid measures

##### Inhalation

Move injured person into fresh air and keep person calm under observation. Get medical attention if any discomfort continues.

<b>Skin contact</b>	Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Get medical attention if any discomfort continues.
<b>4.2. Most important symptoms and effects, both acute and delayed</b>	Severe eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort. Defats the skin. Central nervous system. Headaches, dizziness and nausea. May cause abdominal discomfort if swallowed.
<b>4.3. Indication of any immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Will burn if involved in a fire.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol resistant foam. Dry powder. Carbon dioxide (CO <sub>2</sub> ). Water mist.
<b>Unsuitable extinguishing media</b>	Water jet.
<b>5.2. Special hazards arising from the substance or mixture</b>	During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
<b>Special fire fighting procedures</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Containers close to fire should be removed immediately or cooled with water.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Follow standard emergency procedure. Avoid breathing mist/vapours. Wear appropriate personal protective equipment (See Section 8).
<b>For emergency responders</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Avoid contact with skin and eyes. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
<b>6.2. Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>6.3. Methods and material for containment and cleaning up</b>	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use.
<b>6.4. Reference to other sections</b>	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapours. Avoid contact with skin and eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Provide adequate ventilation. Wear appropriate personal protective equipment. For personal protection, see Section 8 of the SDS. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep container in a well-ventilated place. Store between 15°C - 30°C (60°F - 86°F). Store away from incompatible materials (see section 10 of the SDS).
<b>7.3. Specific end use(s)</b>	Hydraulic fluid in automotive brake/clutch system.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Occupational exposure limits****UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1**

Components	Type	Value
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)	STEL	101.2 mg/m3
		15 ppm
	TWA	67.5 mg/m3
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)		10 ppm
	TWA	50.1 mg/m3
Diethylene glycol (CAS 111-46-6)		10 ppm
	TWA	101 mg/m3
		23 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)****General population**

Components	Value	Assessment factor	Notes
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)			
Long-term, Systemic, Dermal	50 mg/kg bw/day	40	Repeated dose toxicity
Long-term, Systemic, Inhalation	40.5 mg/m3		respiratory tract irritation
Long-term, Systemic, Oral	5 mg/kg bw/day	40	Repeated dose toxicity
Short-term, Local, Inhalation	60.7 mg/m3		respiratory tract irritation
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)			
Long-term, Systemic, Dermal	1.33 mg/kg bw/day	30	Repeated dose toxicity
Long-term, Systemic, Inhalation	30.1 mg/m3		
Long-term, Systemic, Oral	7.5 mg/kg bw/day	120	Repeated dose toxicity
3,6,9,12-Tetraoxahexadecan-1-ol (CAS 1559-34-8)			
Long-term, Systemic, Oral	3 mg/kg bw/day	200	Repeated dose toxicity
Diethylene glycol (CAS 111-46-6)			
Long-term, Local, Inhalation	12 mg/m3	10	respiratory tract irritation
Long-term, Systemic, Dermal	21 mg/kg bw/day	210	Repeated dose toxicity
Long-term, Systemic, Inhalation	12 mg/m3		respiratory tract irritation
Triethylene glycol monobutyl ether (CAS 143-22-6)			
Long-term, Systemic, Dermal	125 mg/kg/day	40	Repeated dose toxicity
Long-term, Systemic, Inhalation	117 mg/m3	10	Repeated dose toxicity
Long-term, Systemic, Oral	12.5 mg/kg/day	40	Repeated dose toxicity
Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate (CAS 30989-05-0)			
Long-term, Systemic, Dermal	10 mg/kg	100	Repeated dose toxicity
Long-term, Systemic, Oral	10 mg/kg	100	Repeated dose toxicity

**Workers**

Components	Value	Assessment factor	Notes
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)			
Long-term, Systemic, Dermal	83 mg/kg bw/day	24	Repeated dose toxicity
Long-term, Systemic, Inhalation	67.5 mg/m3		respiratory tract irritation
Short-term, Local, Inhalation	101.2 mg/m3		respiratory tract irritation
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)			
Long-term, Systemic, Dermal	2.22 mg/kg bw/day	18	Repeated dose toxicity
Long-term, Systemic, Inhalation	50.1 mg/m3		
Diethylene glycol (CAS 111-46-6)			
Long-term, Local, Inhalation	60 mg/m3	2	respiratory tract irritation
Long-term, Systemic, Dermal	43 mg/kg bw/day	105	Repeated dose toxicity
Long-term, Systemic, Inhalation	44 mg/m3		
Triethylene glycol monobutyl ether (CAS 143-22-6)			
Long-term, Systemic, Dermal	208 mg/kg/day	24	Repeated dose toxicity
Long-term, Systemic, Inhalation	195 mg/m3	6	Repeated dose toxicity

Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate (CAS 30989-05-0)

Long-term, Systemic, Dermal 16.7 mg/kg 60 Repeated dose toxicity

**Predicted no effect concentrations (PNECs)**

Components	Value	Assessment factor	Notes
<b>2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)</b>			
Freshwater	1.1 mg/l	1000	
Marine water	0.11 mg/l	10000	
Secondary poisoning	56 mg/kg	90	Oral
Sediment (freshwater)	4.4 mg/kg		
Sediment (marine water)	0.44 mg/kg		
Soil	0.32 mg/kg		
STP	200 mg/l	10	
<b>2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)</b>			
Freshwater	12 mg/l	100	
Intermittent releases	12 mg/l		
Marine water	1.2 mg/l	1000	
Secondary poisoning	0.09 g/kg	200	Oral
Sediment (freshwater)	44.4 mg/kg		
Sediment (marine water)	0.44 mg/kg		
Soil	2.1 mg/kg		
STP	10000 mg/l	1	
<b>3,6,9,12-Tetraoxahexadecan-1-ol (CAS 1559-34-8)</b>			
Freshwater	2.5 mg/l	1000	
Marine water	0.25 mg/l	1000	
Sediment (freshwater)	9.49 mg/kg		
Sediment (marine water)	0.9 mg/kg		
Soil	0.46 mg/kg		
<b>Diethylene glycol (CAS 111-46-6)</b>			
Freshwater	10 mg/l	10	
Intermittent releases	10 mg/l		
Marine water	1 mg/l	100	
Sediment (freshwater)	20.9 mg/kg		
Sediment (marine water)	2.09 mg/kg		
Soil	1.53 mg/kg		
STP	199.5 mg/l	10	
<b>Triethylene glycol monobutyl ether (CAS 143-22-6)</b>			
Freshwater	2 mg/l	50	
Intermittent releases	8.4 mg/l		
Marine water	0.2 mg/l	500	
Secondary poisoning	111 mg/kg	90	Oral
Sediment (freshwater)	7.7 mg/kg		
Sediment (marine water)	0.77 mg/kg		
Soil	0.47 mg/kg		
STP	200 mg/l	10	
<b>Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate (CAS 30989-05-0)</b>			
Freshwater	0.211 mg/l	1000	
Intermittent releases	2.112 mg/l		
Marine water	0.021 mg/l	10000	
Sediment (freshwater)	0.76 mg/kg		
Sediment (marine water)	0.076 mg/kg		
Soil	0.028 mg/kg		
STP	100 mg/l	10	

**Exposure guidelines**

**UK EH40 WEL: Skin designation**

2-(2-Methoxyethoxy)ethanol (CAS 111-77-3) Can be absorbed through the skin.

**8.2. Exposure controls**

**Appropriate engineering controls**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

**Individual protection measures, such as personal protective equipment**

**General information**

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.
<b>Skin protection</b>	
<b>- Hand protection</b>	Wear appropriate chemical resistant gloves. Full contact: Glove material: Butyl rubber. Use gloves with breakthrough time of >480 minutes. Minimum glove thickness 0.3 mm. Nitrile. Use gloves with breakthrough time of > 480 minutes. Minimum glove thickness 0.2 mm. Always wear chemical-resistant protective gloves that comply with EN 374 to handle this product. Observe good industrial hygiene practices and wash gloves with soap and water before removing them. Assess the working conditions and always consult your glove supplier for information on the most suitable type of glove for each task and the required material, thickness, and breakthrough time specifications. The use of type-B gloves in accordance with EN 374 is recommended as a minimum protection against intermittent or splash contact. Consult your supplier to find the most suitable option for the product in question. The requirements of EN 388 must be taken into account for applications involving mechanical hazards with the risk of abrasion or incision. The requirements outlined in EN 407 must be taken into consideration for tasks involving thermal hazards.
<b>- Other</b>	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<b>Respiratory protection</b>	In case of inadequate ventilation or when the product is heated, use suitable respiratory equipment with gas filter (type A2). Respiratory protection should meet standard EN 14387.
<b>Thermal hazards</b>	When material is heated, wear gloves to protect against thermal burns.
<b>Hygiene measures</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.
<b>Environmental exposure controls</b>	Environmental manager must be informed of all major releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Amber.
<b>Odour</b>	Mild.
<b>Odour threshold</b>	Not available.
<b>pH</b>	7 - 10.5
<b>Melting point/freezing point</b>	< -50 °C (< -58 °F)
<b>Initial boiling point and boiling range</b>	> 210 °C (> 410 °F)
<b>Flash point</b>	> 100 °C (> 212 °F)
<b>Evaporation rate</b>	0.01 (n-butylacetate = 100)
<b>Flammability (solid, gas)</b>	Not applicable.

#### Upper/lower flammability or explosive limits

<b>Explosive limit - lower (%)</b>	Property has not been measured.
<b>Explosive limit – upper (%)</b>	Property has not been measured.
<b>Vapour pressure</b>	1 mbar
<b>Vapour density</b>	Property has not been measured.
<b>Relative density</b>	1.01 - 1.06
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Soluble in water.
<b>Partition coefficient (n-octanol/water)</b>	1.5
<b>Auto-ignition temperature</b>	> 280 °C (> 536 °F)
<b>Decomposition temperature</b>	300 °C (572 °F)
<b>Viscosity</b>	Property has not been measured.
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.
<b>9.2. Other information</b>	
<b>Kinematic viscosity</b>	5 - 10 cSt (20 °C (68 °F))

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Stable under normal temperature conditions. Glycol Ethers can form peroxides on storage – do not distil to dryness.
<b>10.3. Possibility of hazardous reactions</b>	Will not occur.
<b>10.4. Conditions to avoid</b>	Avoid exposure to high temperatures or direct sunlight. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong oxidizers, strong acids, and strong bases. Strong reducing agents.
<b>10.6. Hazardous decomposition products</b>	Fire or high temperatures create: Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	Glycol does not easily form a vapour at normal temperatures. Therefore, it must be heated or misted before inhalation exposure can occur.
<b>Skin contact</b>	Prolonged or repeated contact may dry skin and cause dermatitis.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed.

**Symptoms** Severe eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort. Defats the skin. Central nervous system. May cause abdominal discomfort if swallowed. Headaches, dizziness and nausea.

### 11.1. Information on toxicological effects

#### Acute toxicity

Product	Species	Test Results
FERODO Brake Fluid (CAS Mixture)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 3000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
<b>Components</b>		
<b>Species</b>		
<b>Test Results</b>		
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	2700 mg/kg
<b>Oral</b>		
LD50	Rat	4500 mg/kg
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	8980 ml/kg
<b>Oral</b>		
LD50	Rat	6700 ml/kg
Diethylene glycol (CAS 111-46-6)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	16500 mg/kg
Triethylene glycol monobutyl ether (CAS 143-22-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	3540 mg/kg
<b>Oral</b>		
LD50	Rat	5300 mg/kg
<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.	

<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitisation</b>	Based on available data, the classification criteria are not met.
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.
<b>Reproductive toxicity</b>	Suspected of damaging fertility. Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	Based on available data, the classification criteria are not met.
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	Glycol ethers: Some glycol ethers cause adverse effects in animals that include the reproductive system, offspring, blood, kidney and liver.

## SECTION 12: Ecological information

**12.1. Toxicity** Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Components	Species		Test Results
Diethylene glycol (CAS 111-46-6)			
<b>Aquatic</b>			
Algae	NOEC	Algae	100 mg/l, 72 hours
<i>Acute</i>			
Crustacea	EC50	Aquatic invertebrates	100000 mg/l, 24 hours
Fish	LC50	Fish	7520 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	EC50	Aquatic invertebrates	33911 mg/kg/D, 21 days
Triethylene glycol monobutyl ether (CAS 143-22-6)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Pimephales promelas	2400 mg/l, 96 hours

**12.2. Persistence and degradability** Expected to be inherently biodegradable. Expected to be readily biodegradable. (OECD 302B).

**12.3. Bioaccumulative potential** The product is not expected to bioaccumulate.

### Partition coefficient n-octanol/water (log Kow)

FERODO Brake Fluid	1.5
2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)	0.56
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)	-1.18
Diethylene glycol (CAS 111-46-6)	-1.47
Triethylene glycol monobutyl ether (CAS 143-22-6)	0.02

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** This product is water soluble and may disperse in soil.

**12.5. Results of PBT and vPvB assessment** This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6. Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Residual waste** Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



<b>EU waste code</b>	16 01 13* The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

14.1. - 14.6.: Not regulated as dangerous goods.

### RID

14.1. - 14.6.: Not regulated as dangerous goods.

### ADN

14.1. - 14.6.: Not regulated as dangerous goods.

### IATA

14.1. - 14.6.: Not regulated as dangerous goods.

### IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Retained direct EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended**

**- Conditions of restriction given for the associated entry number should be considered**

2-(2-Butoxyethoxy)ethanol (CAS 112-34-5)

2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)

Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate (CAS 30989-05-0)

#### Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

New or expectant mothers should not work with this product if there is a risk due to exposure, in accordance with the Management of Health and Safety at Work Regulations 1999 [SI 1999/3242], as amended.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

**15.2. Chemical safety assessment** No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.  
CAS: Chemical Abstract Service.  
CEN: European Committee for Standardization.  
DNEL: Derived No-Effect Level.  
EC50: Effective Concentration, 50%.  
IATA: International Air Transport Association.  
IMDG: International Maritime Dangerous Goods.  
LC50: Lethal Concentration, 50%.  
LD50: Lethal Dose, 50%.  
MARPOL: International Convention for the Prevention of Pollution from Ships.  
NOEC: No observed effect concentration.  
PBT: Persistent, bioaccumulative and toxic.  
PNEC: Predicted No-Effect Concentration.  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
STEL: Short term exposure limit.  
TWA: Time Weighted Average.  
vPvB: Very persistent and very bioaccumulative.

### References

HSDB® - Hazardous Substances Data Bank  
ECHA: European Chemical Agency.  
Registry of Toxic Effects of Chemical Substances (RTECS)

### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.  
Classification of this product as Serious eye irritation Category 2 (H319) is based on tests conducted on the product as a whole, rather than calculations based on ingredients.

### Full text of any statements, which are not written out in full under sections 2 to 15

H302 Harmful if swallowed.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H360D May damage the unborn child.  
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.  
1, 2, 3, 4, 6, 7, 8, 9, 11, 12, 15, 16.

### This SDS contains revisions in the following section(s):

#### Training information

Follow training instructions when handling this material.

#### Further information

UFI: C300-D0AQ-400U-2MRM, Grade: DOT 3  
UFI: PE00-E039-C00U-Q02V, Grade: DOT 4 – 230

#### Disclaimer

The information provided on this data sheet was abstracted from supplier safety data sheets and standard references in occupational health and toxicology. Federal-Mogul makes no representation or warranty with respect to the information obtained from such references. The information is however, as of the date provided, true and accurate to the best of Federal-Mogul's knowledge, and should be used to make an independent determination of the methods to safeguard workers and the environment.